

Filter Warranty Registration

Date Purchased://		QTY:	
	Size (actual) x xx	Purchase Price \$ \$	Date of Mnf
Name: Address: City, State, Zip:			

SanUVAire, LLC warrants this unit to be free of material and workmanship defects for a five (5) year period after the original date of purchase, under normal use and to the original end-use purchaser.

GENERAL CONDITIONS: If necessary SanUVAire, LLC will repair or exchange, at its option, for the original end-use purchaser, free of charge or pro-rated, FOB factory any unit which is defective in material or workmanship.

This warranty is void if any unit has been subject to abuse, misuse, negligence, unusual operating conditions, accident, careless handling, or improper installation. This warranty is void if the filter has been modified, repaired, tampered with or altered in any way (including the affixing of attachments not provided with the product) by anyone outside of SanUVAire, LLC. This warranty does not cover damage caused by exposure to heat in excess of 130 degrees or exposure to gas, fuel or other oil based solvent.

IN-WARRANTY REPAIRS: For in-warranty repair, return the filter, securely packed, insured (damage occurring during shipment is not covered by this warranty) and postage pre-paid with proof of purchase to:

SanUVAire, LLC 6435 W. Quaker St., Orchard Park, NY 14127

SanUVAire, LLC will not accept collect shipments. There will be a \$10.00 handling charge per filter, any pro-rated amount and return shipping charges. The filter will be returned, COD, on account or prepaid, SanUVAire, LLC option.

IMPORTANT: This warranty is NOT effective unless the Owner Registration section is completely filled in and mailed to us within 45 days of the date of purchase. SanUVAire, LLC authorizes no other warranty. This warranty gives you special legal rights, and you may have other rights which vary from state to state.

Congratulations!!!

INSTALLATION: Simply replace your old filter with your new All American electrostatic air filter. Be sure the arrows on the filter are placed in the same direction as the airflow into your air conditioner.

MAINTENANCE: With proper care and regular cleaning this filter should outlast the unit in which it is installed. It is recommended you clean your filter monthly (more frequently for some applications) by hosing with water, under pressure, to the opposite side from the airflow. If detergent or soap is used, spray it on and let it soak for 15 minutes. RINSE THOROUGHLY with clean water to preserve the electrostatic properties. After rinsing completely, drain the excess water and re-install.

Do NOT spray or coat this filter with oils or adhesives! Do NOT expose to extreme heat or direct sunlight for any extended period of time. Do NOT clean with caustic agents of fuels. C-5 Revised 5/17/2017